

SS16000 Series



Bearing No	Dimensions (mm)				Ball Complement	Maximum speed (r/min)		Weight Kg/pcs
	D	d	B	NO		Grease	Oil	
SS16001	28	12	8	8	4.7630	26000	30000	0.0230
SS16002	32	15	8	9	4.7630	22000	26000	0.0250
SS16003	35	17	8	10	4.7630	20000	24000	0.0320
SS16004	42	20	8	10	5.5560	18000	21000	0.0500
SS16005	47	25	8	11	5.5560	15000	18000	0.0600
SS16006	55	30	9	12	6.3500	13000	15000	0.0850
SS16007	62	35	9	13	6.3500	12000	14000	0.1000
SS16008	68	40	9	15	6.3500	10000	12000	0.1300
SS16009	75	45	10	16	6.3500	9200	11000	0.1700
SS16010	80	50	10	16	7.1440	8400	9800	0.1800
SS16011	90	55	11	16	7.9380	7700	9000	0.2600
SS16012	95	60	11	18	7.1440	7000	8300	0.2800
SS16013	100	65	11	20	7.1440	6500	7700	0.3000
SS16014	110	70	13	15	9.5250	6100	7100	0.4300
SS16015	115	75	13	16	9.5250	5700	6700	0.4600
SS16016	125	80	14	15	11.1120	5300	6200	0.6000
SS16017	130	85	14	16	11.1120	5000	5900	0.6300
SS16018	140	90	16	15	12.7000	4700	5600	0.8500
SS16019	145	95	16	16	12.7000	4500	5300	0.8800
SS16020	150	100	16	17	12.7000	4200	5000	0.9100